

S/N 09/824,903

Response to Office Action Dated 11/03/2005

**In the Claims**

1. (original) A method for calculating look-up tables for a cluster of printers, comprising:

determining a least dynamic printer in the cluster; and  
calculating corrected input values required to normalize an output of at least one non-least dynamic printer in the cluster.

2. (original) The method of claim 1, wherein transfer functions are calculated for each primary color.

3. (cancelled)

4. (original) The method of claim 1, wherein a least dynamic printer is determined for each primary color.

5. (original) The method of claim 1, additionally comprising calculating transfer functions for each printer in the cluster.

6. (original) The method of claim 1, additionally comprising organizing the corrected input values into look-up tables.

S/N 09/824,903

Response to Office Action Dated 11/03/2005

1           7.     (original)   A method for calibrating a cluster of printers,  
2     comprising:

3           printing a calibration target with each printer in the cluster;  
4           measuring each calibration target to produce measurement data;  
5           calculating transfer functions for each printer in the cluster;  
6           determining a least dynamic printer in the cluster;  
7           calculating corrected input values required to normalize output of non-least  
8     dynamic printers in the cluster;  
9           organizing the corrected input values into look-up tables; and  
10          sending the look-up tables to each printer within the cluster.

11  
12  
13          8.     (original)   The method of claim 7, wherein the measuring is  
14     performed by sensors in a paper path of each printer.

15  
16          9.     (original)   The method of claim 7, wherein the measurement data  
17     is expressed in a CIELab context.

18  
19  
20          10.    (original)   The method of claim 7, wherein the calculating steps  
21     are performed on a master printer.

22  
23          11.    (original)   The method of claim 7, wherein the calculating steps  
24     are performed on a print server.  
25

S/N 09/824,903

Response to Office Action Dated 11/03/2005

1  
2 12. (original) The method of claim 7, additionally comprising  
3 incorporating the look-up tables into a color data flow of each printer in the  
4 cluster.

5  
6 13. (original) A method of calibrating a cluster of printers,  
7 comprising:

8 printing a calibration target with each printer in the cluster;

9 measuring each calibration target to produce measurement data;

10 calculating transfer functions for each primary color and for each printer in  
11 the cluster;

12 determining a least dynamic printer in the cluster with respect to each  
13 primary color;

14 calculating corrected input values required to normalize output of non-least  
15 dynamic printers in the cluster to the least dynamic printer in each cluster with  
16 respect to each primary color;

17 organizing the corrected input values into look-up tables; and

18 sending the look-up tables to each printer within the cluster for inclusion in  
19 a color data flow.

20  
21 14. (original) The method of claim 13, wherein the measuring is  
22 performed by sensors in a paper path of each printer.  
23  
24  
25

S/N 09/824,903

Response to Office Action Dated 11/03/2005

1  
2 15. (original) A cluster of printers, comprising:  
3 at least two printers;  
4 a transfer function calculator to derive a transfer function for each printer  
5 with respect to at least one color;  
6 a least dynamic response selector to determine a least dynamic printer from  
7 within the cluster of printers for at least one color;  
8 a normalizer for calculation of corrected input values required to normalize  
9 more dynamic printers' output with respect to the least dynamic printer; and  
10 a look-up table assembler to organize the corrected input values into look-  
11 up tables.  
12  
13

14 16. (original) The method of claim 15, additionally comprising  
15 a file transfer routine to send the look-up tables to each printer within the  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

S/N 09/824,903

Response to Office Action Dated 11/03/2005

17. (original) A computer-readable medium having computer executable instructions thereon which, when executed by a printing system, cause the printing system to:

print a calibration target with each printer in a cluster;  
measure each calibration target;  
calculate transfer functions for each printer in the cluster;  
determine a least dynamic printer in the cluster; and  
calculate corrected input values required to normalize output of non-least dynamic printers in the cluster.

18. (original) The computer-readable medium of claim 17, additionally causing the printing system to organize the corrected input values into look-up tables.

19. (original) The computer-readable medium of claim 18, additionally causing the printing system to send the look-up tables to each printer within the cluster for inclusion in a color data flow.

S/N 09/824,903

Response to Office Action Dated 11/03/2005

1           20.   (original)   A system, comprising:  
2           a transfer function calculator to derive a transfer function for each printer  
3 with respect to at least one color;  
4           a least dynamic response selector to determine a least dynamic printer from  
5 at least two transfer functions for at least one color; and  
6           a normalizer for calculation of corrected input values required to normalize  
7 at least one transfer function with respect to the least dynamic printer.  
8

9  
10          21.   (original)   The calculator of claim 20, additionally comprising:  
11          a look-up table assembler to organize the corrected input values into look-  
12 up tables.  
13

14          22.   (original)   A printer containing the system of claim 20.  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25